AD-A066 789

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO
POWDERED-METAL ALLOY FOR THE PACKING OF GAS TURBINES, (U)
NOV 77 Y N SEMENOV, G L DUBROV
FTD-ID(RS)T-1952-77

F/6 11/6

Ü

UNCLASSIFIED

NL













END DATE FILMED 5-79

FTD-ID(RS)T-1952-77

FOREIGN TECHNOLOGY DIVISION



POWDERED-METAL ALLOY FOR THE PACKING OF GAS TURBINES

by

Yu. N. Semenov, G. L. Dubrov and N. A. Kazantseva





Approved for public release; distribution unlimited.

EDITED TRANSL	ATION	
FTD-ID(RS)T-1952-77	23 Nov ember 19 7	77 -
MICROFICHE NR: 4D-77-C-00	1457	
POWDERED-METAL ALLOY FOR THE PAC		
Yu. N. Semenov, G. L. Dubro N. A. Kazantseva	ov g nd	
21) Edited trans. of #	9 4 May 1967;	/ #
Country of origin: (USSR) Translated by: (Robert D. Hill- Requester: AFML/LLM Approved for public release; dis	stribution unlin	
12 5° P'		ABCESSION for OTIS White Section P BOC Butt Section C UNANIMOUSED JUSTIFICATION
	;	BY BISTRICHTOR/AVAILABILITY CODES BOOK AVAIL and/or SPECIAL
THIS TRANSLATION IS A RENDITION OF THE ORIGI- MAL POREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DI- VISION.	PREPARED BY: TRANSLATION DIVISIO FOREIGN TECHNOLOG WP-AFB, OHIO.	
FTD -ID(RS)T-1952-77	Date 23	Nov 1977

, ll

POWDERED-METAL ALLOY FOR THE PACKING OF GAS TURBINES

Yu.N. Semenov, G.L. Dubrov and

N.A. Kazantseva

Institute of Problems of the Study of Materials of the Academy of Sciences of the USSR

Powdered-metal alloys [cermet alloys] consisting of nickel and boron nitride are well-known. However, at a high temperature they impair the properties of the running-in ability of the packing material.

The proposed alloy is different in that for increasing the heat-resistance, introduced into its composition is silicon within 2-3%, and the remaining components are taken in the following percentage ratio: nickel, 90-93, and boron nitride, 4.5-7, additionally heat-treated at a temperature of 2100-2200°C.

The heat-treated boron nitride powder is mixed with powders of electrolytic nickel and silicon; then they are subjected to pressing, sintering, repressing, and repeated sintering at a temperature of 1100°C for two hours.

The experiments conducted showed that with the additional heat treatment of the boron nitride, there was a significant increase in the heat resistance of the new powdered-metal packing material used in gas turbines.

Object of the Invention

A powdered-metal alloy for the packing of gas turbines, and it contains nickel and boron nitride; it is distinguished by the fact that for the purpose of increasing the heat resistance. introduced into its composition is silicon withing 2-3%, and the remaining components are taken in the following percentage ratio:
• nickel, 90-93, and boron nitride, 4.5-7, additionally heat-treated at a temperature of 2100-2200°C.

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGAN	IZATION	MICROFICHE	ORGAN	IZATION	MICROFICHE
	DMATC DMAAC DIA/RDS-3C USAMIIA BALLISTIC RES LABS	1 2 8 1	E053 E017 E404 E408 E410	AF/INAKA AF/RDXTR-W AEDC AFWL ADTC	1 1 1 1
C510	AIR MOBILITY RAD LAB/FIO	1	E413	ESD FTD	2
C513 C535	PICATINNY ARSENAL AVIATION SYS COMD	1		CCN ETID	1
C591	FSTC	5		NIA/PHS NICD	1 5
C619 D008	MIA REDSTONE NISC	1			
H300 P005	usaice (Usareur) Erda	1			
	CIA/CRS/ADD/SD RDSTA (50L)	1 .			
MABA	'KSI	1			
AFIT/	LD	1			